

## セントロニクスコネクタ 半田付けタイプ、ディップタイプ

日本コネク工業のお届けする57シリーズ、57F、57FEシリーズ、セントロニクスコネクタは高品質、低価格を実現したコネクタです。日本コネク工業の品質管理仕様に基づき管理されておりますので、安心してご使用頂けます。

\*一部シリーズはロックダウンしておりますので、お問い合わせください。



30type

### JC57 Series

#### Specifications

Rated voltage	500V AC (r. m. s)
Rated current	5A / Contact
Dielectric withstanding voltage	1000V AC (r. m. s) / 1 minute
Insulation resistance	1000M Ωmin. at 500V DC
Contact resistance	25m Ωmax.
Operating Temperature	-55℃ ~ +105℃
Applicable cable	AWG#22 (Solid cable) AWG#24 (Standed cable)

#### Item / Material, Finish


Item	Material / Finish
Insulator	PBT Resin 30% Glass (UL94V-0) / Blue
Contact	Copper Alloy / Au Plating
Shell	Steel / Ni Plating
Hood	Steel / Ni Plating
Boot	PVC



10type



20type



40type



60type

Part No	Pole No	Cable Type	Part No	Pole No	Cable Type
JC57-10140	14	Plug for Rack and Panel	JC57-40140	14	Panel Receptacle
JC57-10240	24		JC57-40240	24	
JC57-10360	36		JC57-40360	36	
JC57-10500	50		JC57-40500	50	
JC57-20140	14	Receptacle for Rack and Panel	JC57-60140	14	Receptacle for Cable to Cable
JC57-20240	24		JC57-60240	24	
JC57-20360	36		JC57-60360	36	
JC57-20500	50		JC57-60500	50	
JC57-30140	14	Cable Plug, Top cable entry			
JC57-30240	24				
JC57-30360	36				
JC57-30500	50				

## 57Fセントロニクスコネクタ フラットケーブル圧接タイプ



30type



40type

### JC57F Series

#### Specifications

Rated Voltage	250V AC (r. m. s)
Rated Current	1A / Contact
Dielectric Withstanding Voltage	500V AC (r. m. s) / 1 minute
Insulation Resistance	1000M $\Omega$ min. at 500V DC
Contact Resistance	25m $\Omega$ max.
Operating Temperature	-25°C ~ +85°C
Applicable Cable	Cable pitch:1.27 AWG#28 (Solid cable, Stranded cable) AWG#30 (Solid cable)

#### Item / Material, Finish

Item	Material / Finish
Insulator	PBT Resin (UL94V-0) / Blue
Contact	Copper Alloy / Au Plating
Strain Relief	PBT Resin (UL94V-0) / Blue
Ground Tab	Steel / Ni Plating
Bail Lock	Steel / Ni Plating
Latch	Steel / Ni Plating
Plastic Hood	PBT Resin (UL94V-0) / Blue

Part No	Pole No	Type
JC57F-30140	14	Crimping, witout sheild type
JC57F-30240	24	
JC57F-30360	36	
JC57F-30500	50	
JC57F-40140	14	Crimping, witout sheild type
JC57F-40240	24	
JC57F-40360	36	
JC57F-40500	50	

# 68GF“Ë Å£±‘‹¥‡— ½±ÚÅßÁ³íàíØ°Å°±íßÚcjÁ³íà

41uzqf

51uzqf

## KD68GF!Tfsjft

Tqfdjgdbujpot

Sbufe!Wpmubhf	361W!BD)s/n/t*
Sbufe!Dvssfou	2B!0!Dpoubdu
Ejfmfdusjd!Xjuituboejoh!Wpmubhf	(BD)s/n/t*!0!2!njovuf
Jotvmbujpo!Sftjtubodf	2111N!injo!/!bu!611W!ED
Dpoubdu!Sftjtubodf	36n!inby/
Pqfsbujoh!Ufnqfsbuvsf	.36N!!,96N
Bqqmjdbcmf!Dbcmf	Dbcmf!qjudi;2/38 BXH\$39)Tpmje!dbcmf-Tusboefe!dbcmf* BXH\$41)Tpmje!dbcmf*

Jufn!0!Nbufsjbm-Gjojt

Jufn	Nbufsjbm!0!Gjojt
Jotvmbups	QCU!Sftjo)VM:5W.1*!0!Cmvf
Dpoubdu	Dpqqfs!Bmmpz!0!Bv!Qmbujoh
Tifmm	Tuffm!0!Oj!Qmbujoh
Tusbjo!Sfmjfg	QCU!Sftjo)VM:5W.1*!0!Cmvf
Hspvoe!Ubc	Tuffm!0!Oj!Qmbujoh
Cbjm!MpdI	Tuffm!0!Oj!Qmbujoh
Nfubm!lppe	Bmvnjovn!Bmmpz!0!Hsbz)Pvutjef!Pomz*
Qmbtujd!lppe	BCT!Sftjo!0!Oj!Qmbujoh
Cppu	QWD

Qbsu!Op	Qpmf!Op	Uzqf
KD68GF.412525	Dsjnqjoh-!tifjme!uzqf	
KD68GF.413535		
KD68GF.414747		
KD68GF.416161		
KD68GF.512525	Dsjnqjoh-!tifjme!uzqf	
KD68GF.513535		
KD68GF.514747		
KD68GF.516161		