

ソケット、角ピン Socket, SMT type

1.00mm pitch

Specifications

Current rating : 1.0 A
 Contact resistance : 30mΩ max
 Withstanding Voltage : AC200V 1minute
 Insulation Resistance : 500MΩ
 Operating Temperature : -40℃~+105℃

Materials

Contact Material : Copper Alloy
 Contact Plating : Au over Ni
 Insulator : High temp. thermoplastic

Technical drawing of 10S-S socket showing dimensions: total length L = 1.0 x P, contact length A = 1.0 x (P-1), pin length 1.0, pin size PIN 0.35 x 0.15, and PC dimension with 0.5 offset.

How to order

10S-S XX G-T20

S: Single In Line | Standard plating Ni over Au flash

Number of Positions: P
 S: Single In Line 01 to 20

3D perspective view of 10S-S socket with dimensions: 1.5, 1.8, 2.4, 3.0.

Technical drawing of 10S-D socket showing dimensions: total length L = 1.0 x P/2, contact length A = 1.0 x (P/2 - 1), pin length 1.0, pin size PIN 0.35 x 0.15, and PC dimension with 0.5 offset and diameter 0.6.

How to order

10S-D XX G-T20

D: Dual In Line | Standard plating Ni over Au flash

Number of Positions: P
 D: Dual In Line 02 to 40

3D perspective view of 10S-D socket with dimensions: 1.8, 2.4, 3.9, 2.5, 0.5.

*最小ご注文数は、製造状況 お取引条件により変動することがありますので、事前に御確認ください。